

Characteristics

The direct operated control valve D1FP of the nominal size NG06 (CETOP 03) shows extremely high dynamics combined with maximum flow. It is the preferred choice for highest accuracy in positioning of hydraulic axis and controlling of pressure and velocity.





Driven by the patented VCD® actuator the D1FP reaches the frequency response of real servovalves. Compared with solenoid driven valves the D1FP can also be used in applications with pressure drops up to 350 bar across the valve. Because of the high flow capability the D1FP can be a substitute for NG10 valves in some cases.

At power-down the spool moves in a defined position. All common input signals are available.


3

Features

- Real servovalve dynamics (-3 dB / 350 Hz at ±5 % input signal)
- No flow limit up to 350 bar pressure drop through the valve
- Max. tank pressure 350 bar (with external drain port y)
- High flow
- Defined spool positioning at power-down - optional P-A/B-T or P-B/A-T or center position (for overlapped spools)
- Onboard electronics



Ordering Code



Code	Spool type	Flow [l/min] at Δp 35 bar per metering edge
Zerolap		
E50B		3
E50C		6
E50F		12
E50G		16
E50H		25
E50M		40
B60C		6 / 3
B60F		12 / 6
B60G		16 / 8
B60H		25 / 12.5
B60M		40 / 20
Underlap		
E55B		3
E55C		6
E55F		12
E55G		16
E55H		25
E55M		40
Overlap		
E01B		3
E01C		6
E01F		12
E01G		16
E01H		25
E01M		40
B31C		6 / 3
B31F		12 / 6
B31G		16 / 8
B31H		25 / 12.5
B31M		40 / 20
E02B		3
E02C		6
E02F		12
E02G		16
E02H		25
E02M		40
B32C		6 / 3
B32F		12 / 6
B32G		16 / 8
B32H		25 / 12.5
B32M		40 / 20

Code	Connection type
0	6 + PE acc. EN175201-804
5	11 + PE acc. EN175201-804
7	6 + PE + Enable

Code	Signal	Function
B	+/- 10 V	0...+10 V -> P-A
E	+/- 20 mA	0...+20 mA -> P-A
S	4...20 mA	12...20 mA -> P-A

Code	Seals
N	NBR
V	FPM
H	for HFC fluid

Code	Spool position at power down
A ²⁾	
B ²⁾	
C ³⁾	
H ⁴⁾	
J ⁴⁾	

Short delivery time for all variations

Note:

Adapter plate for ISO 4401 to ISO 10372 size 04, Ordering code HAP04WV06-1661

Please order connector separately, see chapter 3 accessories.

Parametrizing cable OBE -> RS232, item no. 40982923

- ¹⁾ On power down the spool moves in a defined position. This cannot be guaranteed in case of single flow path on the control edge A – T resp. B – T with pressure drops above 120 bar or contamination in the hydraulic fluid.
- ²⁾ Approx. 10 % opening, only zero lapped spools and underlap spools.
- ³⁾ Only for overlapped spools.
- ⁴⁾ Not for flow code M (40 l/min).
- ⁵⁾ Plug in the Y-port needs to be removed at tank pressure >35 bar.



3

General			
Design	Direct operated servo proportional DC valve		
Actuation	VCD® actuator		
Size	NG06 / CETOP 03 / NFPA D03		
Mounting interface	DIN 24340 / ISO 4401 / CETOP RP121 / NFPA		
Mounting position	unrestricted		
Ambient temperature	[°C]	-20...+50	
MTTF _D value ¹⁾	[years]	150	
Weight	[kg]	5.0	
Vibration resistance	[g]	10 Sinus 5...2000 Hz acc. IEC 68-2-6 30 Random noise 20...2000 Hz acc. IEC 68-2-36 15 Shock acc. IEC 68-2-27	
Hydraulic			
Max. operating pressure	[bar]	Ports P, A, B 350, port T 35 for internal drain, 350 for external drain, port Y 35 ²⁾	
Fluid	Hydraulic oil according to DIN 51524 ... 535, other on request		
Fluid temperature	[°C]	-20...+60 (NBR: -25...+60)	
Viscosity permitted	[cSt]/mm ² /s	20...400	
Viscosity recommended	[cSt]/mm ² /s	30...80	
Filtration	ISO 4406 (1999); 18/16/13		
Nominal flow at Δp=35 bar per control edge ³⁾	[l/min]	3 / 6 / 12 / 16 / 25 / 40	
Flow maximum	[l/min]	90 (at Δp=350 bar over two control edges)	
Leakage at 100 bar	[ml/min]	<400 (zerolap spool); <50 (overlap spool)	
Opening point	[%]	set to 23 commande signal (see flow characteristics)	
Static / Dynamic			
Step response at 100 % step ⁴⁾	[ms]	<3.5	
Frequency response (±5 % signal) ⁴⁾	[Hz]	350 (amplitude ratio -3 dB), 350 (phase lag -90°)	
Hysteresis	[%]	<0.05	
Sensitivity	[%]	<0.03	
Temperature drift	[%/K]	<0.025	
Electrical characteristics			
Duty ratio	[%]	100	
Protection class	IP65 in accordance with EN 60529 (with correctly mounted plug-in connector)		
Supply voltage/ripple	[V]	DC 22 ... 30, electric shut-off at < 19, ripple < 5 % eff., surge free	
Current consumption max.	[A]	3.5	
Pre-fusing	[A]	4.0 medium lag	
Input signal			
Code B	Voltage	[V]	10...0...-10, ripple <0.01 % eff., surge free, 0...+10 V P->A
	Impedance	[kOhm]	100
Code E	Current	[mA]	20...0...-20, ripple <0.01 % eff., surge free, 0...+20 mA P->A
	Impedance	[Ohm]	250
Code S	Current	[mA]	4...12...20, ripple <0.01 % eff., surge free, 12...20 mA P->A <3.6 mA = disable, >3.8 mA = according to NAMUR NE43
	Impedance	[Ohm]	250
Differential input max.			
	Code 0	[V]	30 for terminal D and E against PE (terminal G)
	Code 5	[V]	30 for terminal 4 and 5 against PE (terminal ⊥)
	Code 7	[V]	30 for terminal D and E against PE (terminal G)
Enable signal (only code 5/7)	[V]	5...30, Ri = 9 kOhm	
Diagnostic signal	[V]	+10...0...-10 / +12.5 error detection, rated max. 5 mA	
EMC	EN 61000-6-2, EN 61000-6-4		
Electrical connection	Code 0/7	6 + PE acc. EN 175201-804	
	Code 5	11 + PE acc. EN 175201-804	
Wiring min.	Code 0/7	[mm ²]	7x1.0 (AWG 16) overall braid shield
	Code 5	[mm ²]	8x1.0 (AWG 16) overall braid shield
Wiring length max.	[m]	50	

¹⁾ If valves with onboard electronics are used in safety-related parts of control systems, in case the safety function is requested, the valve electronics voltage supply is to be switched off by a suitable switching element with sufficient reliability.

²⁾ For applications with p_r>35 bar (max. 350 bar) the Y-port has to be connected and the plug in the Y-port has to be removed.

³⁾ Flow rate for different Δp per control edge: $Q_x = Q_{Nom.} \cdot \sqrt{\frac{\Delta p_x}{\Delta p_{Nom.}}}$


⁴⁾ Measured with load (100 bar pressure drop/two control edges).

Flow curves


(Overlapped spool set to opening point 23 %)

at $\Delta p = 35$ bar per metering edge


Spool type **E01/E50**



Spool type **B31/B60**




Pressure gain



Functional limits

at 25 %, 50 %, 75 % and 100 % command signal


Spool type **E01M/E50M**



Frequency response

± 5 % command signal


± 90 % command signal



All characteristic curves measured with HLP46 at 50 °C.


Code 0

Parametrizing cable
 3 m length
 Item no.: 40982923




Code 5

Parametrizing cable
 3 m length
 Item no.: 40982923



Code 7

Parametrizing cable
 3 m length
 Item no.: 40982923



ProPxD interface program

The ProPxD software allows quick and easy setting of the digital valve electronics. Individual parameters as well as complete settings can be viewed, changed and saved via the comfortable user interface. Parameter sets saved in the non-volatile memory can be loaded to other valves of the same type or printed out for documentation purposes.

The PC software can be downloaded free of charge at www.parker.com/euro_hcd – see page "Support" or directly at www.parker.com/propxd.


Features

- Comfortable editing of valve parameters
- Saving and loading of customized parameter sets
- Executable with all Windows® operating systems from Windows® XP upwards
- Simple communication between PC and valve electronics via serial interface RS232C




The valve electronics cannot be connected to a PC with a standard USB cable – this can result in damages of PC and/or valve electronics.






The parametrizing cable may be ordered under item no. 40982923.

3



3



Surface finish	 Kit	 Kit	 Kit	 Kit
	BK375	4x M5x30 ISO 4762-12.9	7.6 Nm ±15 %	NBR: SK-D1FP FPM: SK-D1FP-V HFC: SK-D1FP-H